

Winkelgelenke SA PM08-02-502-DURBAL - PM08-02-502-DURBAL

<https://www.123kugellager.at/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/pm08-02-502-durbal>

PM08-02-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]					measurements [mm]					weight		calculation factors		rotational speed limit		basic load rating		
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min-1]	C [N]	C0 [N]	dyn.	stat.	C0 [N]	C0 [N]	
PM 08-02	-502	8	M 12 x 1.5	11,0	30	17	15	10												
type		l1	l2	l3	h1	h2	u	z	alpha [°]	alpha prime [°]										
PM 08	23	20	48,5	2,0	2,5	8,5	0,088	1,9	1,81	1225	2605	985								

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952507521
Innendurchmesser	8 mm
Außendurchmesser	30 mm
Dicke	15 mm
Typ	SA
Gewicht	88 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE