

Winkelgelenke SA

BRM12-60-502-DURBAL - BRM12-60-502-DURBAL

<https://www.123kugellager.at/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/brm12-60-502-durbal>

BRM12-60-502



male thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

rod end housing:
stainless steel 1.4034, hardened, bearing race superfinished, rolled thread

inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3402 D1/L6 (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]						
type	left-hand thread	d ₁	d ₂	d ₄	d ₅	b ₁	b ₂	h
BRM 12 -60	-502	12	M 12	14,5	32	16	12,0	54
measurements [mm]		weight		calculation factors	rotational speed limit	basic load rating		
type	l	l ₂	α [°]	W [kg]	Y	v _{max} [min ⁻¹]	C [N]	C ₀ [N]
BRM 12	33	19	7,5	0,087	1,74	1,82	1125	3450 1250

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952509143
Innendurchmesser	12 mm
Außendurchmesser	32 mm
Dicke	16 mm
Typ	SA
Gewicht	87 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE