

Rillenkugellager einreihig 3004-SS-NICE - 3004-SS-NICE

<https://www.123kugellager.at/kugellager-gehauselager/rillenkugellager/einreihig/3004-ss-nice>

3000 Series® Semi-Ground Radial Bearings **NICE®**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3004™					SS	+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.015 -0.015

WIDTH		BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
B (in) (mm)	C (lbs) (N)	Co (lbs) (N)	W (lb) (kg)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)	
0.2813 ⓐ 7.1450	325 1448	255 1135	0.03 0.01	0.474 12.04	0.778 19.76	0.015 0.38	

ⓐ Width for sealed versions = 0.3438 (8.733) ⓑ Weights given are for greased and sealed versions
ⓐ 3038 and larger +.0000/-0.006 (-.000/-0.15)

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952558110
Innendurchmesser	9.525 mm
Innendurchmesser	3/8" inch
Außendurchmesser	22.225 mm
Außendurchmesser	7/8" inch
Dicke	7.145 mm
Dicke	0.281" inch
Gewicht	10 g
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE