


# Rillenkugellager einreihig 3007-NS-NICE - 3007-NS-NICE

<https://www.123kugellager.at/kugellager-gehauselager/rillenkugellager/einreihig/3007-ns-nice>

**3000 Series® Semi-Ground Radial Bearings** **NICE®**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- W/LOW RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm) +0.005 +0.13 -0.00 -0.005 -0.13	O.D. D (in) (mm) +0.000 +0.00 -0.000 -0.015 -0.015
3007™					NS	0.4375 11.113	0.9063 23.020

BASIC LOAD RATINGS		WEIGHT		ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm) +0.005 +0.00 -0.005 -0.13	DYNAMIC C (lbs) (N)	STATIC Co (lbs) (N)	W O (lbs) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.3125 7.938	350 1558	300 1355	0.03 0.01	0.517 13.13	0.778 19.76	0.015 0.38

Ⓞ Weights given are for greased and sealed versions  
Ⓞ 3038 and larger +0.000/-0.005 (+0.00/-0.15)

## PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952558295
Innendurchmesser	11.113 mm
Außendurchmesser	23.02 mm
Dicke	7.938 mm
Gewicht	10 g
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE