

# Rillenkugellager einreihig 3023-SC-NICE - 3023-SC-NICE

<https://www.123kugellager.at/kugellager-gehauselager/rillenkugellager/einreihig/3023-sc-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3023™		SC				+0.005 +0.13 -0.000 -0.000	+0.000 +0.00 -0.013 -0.005
						0.6250 15.875	1.3750 34.925

WIDTH B (in) (mm)	BASIC LOAD RATINGS		WEIGHT W <sup>⓪</sup> (lb) (kg)	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lb) (N)	STATIC C <sub>0</sub> (lb) (N)		d <sub>a</sub> min (in) (mm)	D <sub>a</sub> max (in) (mm)	r max (in) (mm)
0.4375 11.113	940 4183	860 3783	0.10 0.05	0.753 19.13	1.203 30.58	0.025 0.64

<sup>⓪</sup> Weights given are for greased and sealed versions  
<sup>⓪</sup> 3028 and larger +0.0005/-0.005 (+0.001/-0.13)

## PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952558561
Innendurchmesser	15.875 mm
Außendurchmesser	34.925 mm
Dicke	11.113 mm
Gewicht	50 g
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE