


# Rillenkugellager einreihig 3035-NS-NICE - 3035-NS-NICE

<https://www.123kugellager.at/kugellager-gehauselager/rillenkugellager/einreihig/3035-ns-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3035™						+0.005 +0.13 -0.000 -0.005	+0.000 +0.00 -0.0005
					NS	0.7500 19.050	1.7000 44.450

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Ca (lb) (N)	W <sup>⓪</sup> (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.5000 12.700	1300 5795	1025 4561	0.20 0.09	0.965 24.51	1.530 38.98	0.025 0.64

<sup>⓪</sup> Weights given are for greased and sealed versions  
<sup>Ⓢ</sup> 3035 and larger +.0005/-0.005 (+.000/-0.13)

## PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952558790
Innendurchmesser	19.05 mm
Außendurchmesser	44.45 mm
Dicke	12.7 mm
Gewicht	90 g
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE