


Rillenkugellager einreihig 7520-DL-NICE - 7520-DL-NICE

<https://www.123kugellager.at/kugellager-gehauselager/rillenkugellager/einreihig/7520-dl-nice>

7500 Series™ Heavy Duty Precision Ground Radial Bearings **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- HIGH SPEED RANGE: 3000 - 5000 RPM
- THROUGH HARDENED BEARING STEEL
- POLISHED GROOVES
- WIDER RETAINER STANDARDS
- DOUBLE SEALED VERSIONS
- SPECIAL OPERATING MODES: 1/2 CONTACT BALL WITH THIN LUBRICANT FILM
- AVAILABLE WHILE MOUNTED OR OPEN
- ALL BEARINGS HAVE 3 RING AND GROOVE ROLLING SURFACES
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION, SHOCK AND VIBRATION ARE CONCERNS



BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	INNER WIDTH C (in) (mm)	F (in) (mm)
7520™	+0.000 -0.005 -0.013	+0.000 -0.005 -0.015	+0.000 -0.005 -0.005	0.025 1.59	0.8750 22.23	1.672 42.47

PRINCIPLE DIMENSIONS			BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
G (in) (mm)	H (in) (mm)	J (in) (mm)	A (in) (mm)	Dynamic C (lb) (N)	Static C ₀ (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
4.83	1.65	2.7856	0.035	6360	2620	0.67	1.500	2.312	0.036
		70.25	0.89	23852	11659	0.26	38.10	58.72	0.89

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)
 ② Tolerance for 7514™ and larger is +0.000/-0.005 (+.000/-0.015)
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of FSC Nide® Bearings.

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3616060473332
Innendurchmesser	31.75 mm
Außendurchmesser	65.09 mm
Dicke	19.05 mm
Gewicht	260 g
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE