

Stehlagereinheiten / Flanschlagereinheiten 2 loch N6906-B-NICE - N6906-B-NICE

https://www.123kugellager.at/kugellager-gehauselager/gehauselager/stehlagereinheiten-flanschlagereinheiten-2loch/n6906-b-nice

6900

**Series™ Semi-Ground Radial Bearings,
Extended Inner with Flanged Housing**

NICE

- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 3000 - 3000 RPM
- THROUGH HARDNESS
- RETAINER DESIGN
- NYLON RETAINER STANDARD
- SHOULD BE OILED STANDARD
- EXTENDED INNER RING WITH TWO BOLT SLOTS
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGE

① When Ordering specify whether assembly of bearing only is required.
Bearings are stamped with designation and a "B" for example 6906™B. Housing's no longer carry these numbers.
② Tolerance for 6912 and larger is .0000-.0004 (-0.001-.016)

BEARING		PRINCIPLE DIMENSIONS					
FLANGED BEARING UNIT	BEARING ONLY SUFFIX	Bore d (in) (mm)	O.D. D (in) (mm)	Width B (in) (mm)	Width E (in) (mm)	E (in) (mm)	F (in) (mm)
N6906™	B	0.375 9.53	0.9063 23.020	0.313 7.94	0.688 17.46	0.555 14.10	0.375 9.53

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3616060473349
Durchmesser der Welle	9.53 mm
Durchmesser der Welle	3/8" inch
Anzahl der Befestigungen	2
Befestigung	blockierschraube
Befestigungsabstand	47.63 mm
Befestigungsabstand	1 7/8" inch
Material	TOLE
Gewicht	30 g
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE