

# Stehlagereinheiten / Flanschlagereinheiten 2 loch N6908-B-NICE - N6908-B-NICE

https://www.123kugellager.at/kugellager-gehauselager/gehauselager/stehlagereinheiten-flanschlagereinheiten-2loch/n6908-b-nice

**6900 Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing NICE**

- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE - 3000 - 8000 RPM
- THROUGH HARDNESS
- RETAINER DESIGN
- SYLON RETAINER STANDARD
- SHOULDER BEADED STANDARD
- EXTENDED INNER RING WITH TWO BEZEL EDGES
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGES

When Ordering specify whether assembly of bearing only is required.  
Bearings are stamped with designation and a "B" for example 6908™B. Housing's no longer carry size numbers.  
Tolerance for 6912 and larger is  $\pm 0.0001$  (-0.0001-0.015)

BEARING		PRINCIPLE DIMENSIONS					
		Bore d (in) (mm)	O.D. D (in) (mm)	Width B (in) (mm)	Width C (in) (mm)	E (in) (mm)	F (in) (mm)
FLANGED BEARING UNIT	BEARING ONLY	+0.005 -0.015	+0.000 +0.005	+0.000 +0.005			
	SUFFIX	-0.000 -0.005	-0.000 -0.005	-0.005 -0.010			
N6908™	B	0.500 12.70	1.6250 41.28	0.900 22.70	1.000 25.40	0.955 24.28	0.500 12.70

## PRODUKTMERKMALE

Marke	NICE
N° Ean13	3616060473356
Durchmesser der Welle	12.7 mm
Anzahl der Befestigungen	2
Befestigung	blockierschraube
Befestigungsabstand	73.03 mm
Material	TOLE
Gewicht	160 g
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE