

# Zubehör

## 7611-DL-NICE - 7611-DL-NICE

<https://www.123kugellager.at/kugellager-gehauselager/gehauselager/zubehor/7611-dl-nice>

**7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring NICE™**

- PRECISION GRINDING ON ALL CONTACT SURFACES - OPTIMUM TO THE BEARING DESIGN
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 5000-8000 RPM
- TIMOTHY HARDENED
- STEEL BEARING
- STYLISH CASE STANDARD
- SHOULD BE OILED
- EXCELLENT APPLICABLE SINGLE LIP CONTACT
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHIP FUL CRATE - THIS WILL BE AVAILABLE AS AN OPTION
- RECOMMENDED FOR APPLICATIONS WHERE EFFICIENCY, WEIGHT AND NOISE ARE CRITICAL

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7611™	.8675 17.46	1.7500 44.50	0.6250 15.88	0.0625 1.59	1.000 25.40	0.138 3.49

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C <sub>d</sub> (lbf) (N)	Static C <sub>s</sub> (lbf) (N)	W (lb) (kg)
0.042 1.07	1.922 48.82	1.992 50.74	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2196 11548	1025 4581	0.30 0.14

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)      ② Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear  
 ③ Tolerance for 7613™ and larger is +.0000-.0006 (+.0000-.015)      ④ Weights given are for greased and sealed versions  
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

## PRODUKTMERKMALE

Marke	NICE
N° Ean13	3616060473424
Innendurchmesser	17.46 mm
Außendurchmesser	25.63 mm
Dicke	15.88 mm
Gewicht	140 g
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE