

Zubehör

7613-DL-NICE - 7613-DL-NICE

<https://www.123kugellager.at/kugellager-gehauselager/gehauselager/zubehor/7613-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring **NICE™**

- PRECISION GRINDING ON ALL CONTACT SURFACES - FINISH TO THE TOLERANCES SHOWN
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 5000-8000 RPM
- TIMEDUR HARDENED
- STEEL BEARING
- STYLISH CASE STANDARD
- SHRINK BEARING
- EXCELLENT APPLICABLE SINGLE LIP CONTACT TIME
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHIP FUL CRANK. THIS WILL CHANGE TO AN OPTION
- RECOMMENDED FOR APPLICATIONS WHERE EXCESSIVE HEAT AND VIBRATION ARE REQUIRED.

BEARING	PRINCIPLE DIMENSIONS					
	SOBE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7613™	.8125 20.64	2.5000 63.50	0.6250 15.88	0.0625 1.58	1.306 33.17	0.138 3.45

PRINCIPLE DIMENSIONS							BASIC LOAD RATINGS		WEIGHT
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws	Radius R (in) (mm)	Dynamic C _d (lbf) (N)	Static C _s (lbf) (N)	W (lb) (kg)
0.042 1.07	2.156 54.77	1.179 29.95	0.482 12.50	0.261 6.63	1/4-28	0.036 0.89	2970 13217	1300 6008	0.45 0.20

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG) ② Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ③ Tolerance for 7613™ and larger is +.0000-.0006 (+.0000-.015) ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3616060473448
Innendurchmesser	20.64 mm
Außendurchmesser	33.17 mm
Dicke	15.88 mm
Gewicht	200 g
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE