

Gelenkköpfe TSM

MS-05-F-DUNLOP - MS-05-F-DUNLOP

<https://www.123kugellager.at/kugellager-gehauselager/gelenkkopfe-gelenklager/tsm/ms-05-f-dunlop>

MALE ROD ENDS DUNLOP



MS SERIES: MS - MSS - MS SS

Description:
MS Series is our 3-piece steel on steel range of male rod ends incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and medium to heavy mechanical load applications requiring low friction, available in both metric and imperial bore thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 230M07Ph and forged 60MnA, zinc plated and clear trivalent passivate and stainless steel 303, and forged 304. Inner Ring: Steel 670M20 zinc plated and clear trivalent passivate. Liner: High strength PTFE bronze mesh composite. Ball: Bearing steel 100Cr6 heat treated, polished & electroless nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes, low friction, high shock loads, Extended wear life, No maintenance, Studded and stainless steel options.

Possible Applications:
Medium heavy industrial mechanical applications, Construction equipment, Agricultural equipment, Motor sport and recreational vehicles requiring high precision motion control.

Temperature Range:
-200°C to +260°C

Specifications:
ELV & RoHS compliant

Housing: Steel 230M07Ph (Sizes 04 - 07) Forged 60MnA (Sizes 08-12) Zinc Plated and Clear Trivalent Passivate

Inner Ring: Steel 670M20, Zinc Plated and Clear Trivalent Passivate

Balls: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Liners: High Strength PTFE Composite

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MS-05F		5/16	5/16 BSF	0.437	0.344	1.000	1.875	1.250	11.35	11,100

Interchange table

Dunlop	Rose	Aurora	Askubal	SKF	ASAHI	IKO	Fluro
MS-M (metric)	MNC	MM-M-T and MB-M-T	KA-P	SAKB-P	JAM-EC	POS-EC	GASW
MS (imperial)	RMC	MM-T and MB-T	-	-	-	POSB-EC	-

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

For stainless steel add 'SS' to part no. For example 'MS-04 SS'

MS SERIES: MS - MSS - MS SS

Description:
MS Series is our 3-piece steel on steel range of male rod ends incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and medium to heavy mechanical load applications requiring low friction, available in both metric and imperial bore thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 230M07Ph and forged 60MnA, zinc plated and clear trivalent passivate and stainless steel 303, and forged 304. Inner Ring: Steel 670M20 zinc plated and clear trivalent passivate. Liner: High strength PTFE bronze mesh composite. Ball: Bearing steel 100Cr6 heat treated, polished & electroless nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes, low friction, high shock loads, Extended wear life, No maintenance, Studded and stainless steel options.

Possible Applications:
Medium heavy industrial mechanical applications, Construction equipment, Agricultural equipment, Motor sport and recreational vehicles requiring high precision motion control.

Temperature Range:
-200°C to +260°C

Specifications:
ELV & RoHS compliant

Housing: Steel 230M07Ph (Sizes 04 - 07) Forged 60MnA (Sizes 08-12) Zinc Plated and Clear Trivalent Passivate

Inner Ring: Steel 670M20, Zinc Plated and Clear Trivalent Passivate

Balls: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Liners: High Strength PTFE Composite

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MS-05F		5/16	5/16 BSF	0.437	0.344	1.000	1.875	1.250	11.35	11,100

Interchange table

Dunlop	Rose	Aurora	Askubal	SKF	ASAHI	IKO	Fluro
MS-M (metric)	MNC	MM-M-T and MB-M-T	KA-P	SAKB-P	JAM-EC	POS-EC	GASW
MS (imperial)	RMC	MM-T and MB-T	-	-	-	POSB-EC	-

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

For stainless steel add 'SS' to part no. For example 'MS-04 SS'

PRODUKTMERKMALE

Marke	DUNLOP
N° Ean13	3616060549402
Innendurchmesser	7.9375 mm
Innendurchmesser	5/16" inch
Außendurchmesser	25.4 mm
Außendurchmesser	1" inch
Dicke	11.0998 mm
Dicke	0.437" inch
Typ	TSM
Gewinde	Rechtsgewinde
Schmierung	mit
Statische Belastung	0.0111 kN
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE