

Gelenkköpfe SI FX-M12-G-DUNLOP - FX-M12-G-DUNLOP

<https://www.123kugellager.at/kugellager-gehauselager/gelenkkopfe-gelenklager/si/fx-m12-g-dunlop>

FEMALE ROD ENDS **DUNLOP**



FX SERIES

Description:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: S17M 4J, heat treated to 50/50 tons/in² tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available. Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications. Construction equipment. Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged S17M4J, heat treated to 50/50 tons/in² tensile all over, Phosphated all over.

Ball: Bearing Steel 100Cr6, Heat Treated and Phosphated all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	J	M	X	Static Load Rating (Newtons) Radial
FX-M12G		12	19.0	16.2	19.0	41.2	54.2	28.0	20.3	M12 x 1.75	22	49000

Interchange table

Dunlop	Rose	NMB
FX-M (metric)	RBJ-M	RBJ-M
FX (imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUKTMERKMALE

Marke	DUNLOP
N° Ean13	3616060555069
Innendurchmesser	12 mm
Außendurchmesser	19 mm
Dicke	16.02 mm
Typ	SI
Gewinde	Rechtsgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE