


Gelenkköpfe SI

AL-SA-019-LH-DUNLOP - AL-SA-019-LH-DUNLOP

<https://www.123kugellager.at/kugellager-gehauselager/gelenkkopfe-gelenklager/si/al-sa-019-lh-dunlop>

FEMALE ROD ENDS



AL SERIES

Description:
AL-Series is our 3-piece aluminum light weight range of self-lubricating general purpose female rod ends suitable for light industrial/mechanical load applications requiring low friction, with good wear resistance and available in metric bore and thread sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Aluminum A6061, black anodized. Race: GR-nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features:
Metric bore & thread sizes
Low friction
Self-lubricating
Good wear resistance
Excellent moisture resistance
No maintenance
Light weight

Possible Applications:
Light industrial/mechanical applications
Weight restricted applications
Linear movement sensors

Temperature Range:
-30°C to +170°C

Specification:
ELV & RoHS compliant

Housing: Aluminum A6061, Black Anodized Race Ball: GR-nylon, LV-3H Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

| Part No. Right Hand | Part No. Left Hand | Bore Size | Thread | W | H | D | L1 | L2 | O | AF | Static Load Rating Radial (Newtons) |
|---------------------|--------------------|-----------|---------|---|------|----|------|-----|-----|-----|-------------------------------------|
| AL-SA-019-LH | | 9 | M9x0.90 | 8 | 8.00 | 16 | 18.0 | 6.5 | 9.0 | 9.0 | 5,340 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | DUNLOP |
| N° Ean13 | 3616060556462 |
| Innendurchmesser | 5 mm |
| Innendurchmesser | 0.197" inch |
| Außendurchmesser | 8 mm |
| Außendurchmesser | 0.315" inch |
| Dicke | 6 mm |
| Dicke | 0.236" inch |
| Typ | SI |
| Gewinde | Rechtsgewinde |
| Schmierung | mit |
| Verpackung | 1 |

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE