

# Winkelgelenke SA FSX-10-8-DUNLOP - FSX-10-8-DUNLOP

<https://www.123kugellager.at/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/fsx-10-8-dunlop>

**FEMALE ROD ENDS**



**FSX SERIES**

**Description:**  
FSX series is our 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

**Material Specifications:**  
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate  
Inner Ring: Steel 070M20, Zinc Plated and Clear Trivalent Passivate  
Ball: 100Cr6 heat treated, polished and electroless Nickel plated and stainless steel 304C  
Liner: High strength PTFE bronze mesh composite.

**Features:**  
Metric & Imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

**Temperature Range:**  
-200°C to +240°C

**Possible Applications:**  
Motorsport and heavy industrial mechanical applications.

**Specifications:**  
ELV & RoHS compliant applications.

**Housing:** Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate

**Inner Ring:** Steel 070M20, Zinc Plated and Clear Trivalent Passivate

**Ball:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

**Liner:** High Strength PTFE Composite

**Temp Range:** -200°C to +240°C

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSX-10-8		1/2	5/8 UNF	0.750	0.542	1.750	2.500	1.500	0.875	67500

**Interchange table**

Dunlop	Aurora	Fluro
FSX-M (Metric)	AM-M-T and AD-M-T	GUSW
FSX (Imperial)	AM-T and AD-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## PRODUKTMERKMALE

Marke	DUNLOP
N° Ean13	3616060558619
Innendurchmesser	12.7 mm
Außendurchmesser	44.45 mm
Dicke	19.05 mm
Typ	SA
Gewinde	Rechtsgewinde
Schmierung	NA
Statische Belastung	67.5 kN
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE