

Nadelhülsenlager BA78-Z-IKO - BA78-Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/ba78-z-iko>



| Boundary dimensions mm(inch) | | | Standard mounting dimensions mm | | | | Basic dynamic load rating | Basic static load rating | Allowable rotational speed(l) | Assembled inner ring |
|------------------------------|----------------|----------------|---------------------------------|-------------|-------------|-------------|---------------------------|--------------------------|-------------------------------|----------------------|
| F_w | D | C | r_1 | r_2 | J | C | C_0 | | | |
| 11.112 (0.44) | 15.875 (0.625) | 12.700 (0.500) | Min. 0 | Max. 11.112 | Min. 11.101 | Max. 15.865 | Min. 15.867 | 4490 | 5130 | 35000 |

PRODUKTMERKMALE

| | |
|----------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3616060603029 |
| Innendurchmesser | 11.112 mm |
| Außendurchmesser | 15.875 mm |
| Dicke | 12.7 mm |
| Grenzdrehzahl | 35000 rpm |
| Dynamische Belastung | 4.46 kN |
| Statische Belastung | 5.13 kN |
| Verpackung | 1 |

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE