

Nadelhülsenlager BA148-Z-IKO - BA148-Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/ba148-z-iko>



| Boundary dimensions mm(inch) | | | Standard mounting dimensions mm | | | | Basic dynamic load rating | Basic static load rating | Allowable rotational speed | Assembled outer ring |
|------------------------------|----------------|-------------|---------------------------------|--------|--------|----------------|---------------------------|--------------------------|----------------------------|----------------------|
| P_{10} | D | C | d_2 | s_4 | J | C | C_0 | rpm | | |
| 22.225 (A 8) | 28.575 (1 1/8) | 12.75 (500) | 2.6 | 22.225 | 22.212 | 28.587 (1 1/8) | 28.566 | 7440 | 10100 | 18000 (RB 198) |

PRODUKTMERKMALE

| | |
|----------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3616060603296 |
| Innendurchmesser | 22.225 mm |
| Außendurchmesser | 28.575 mm |
| Dicke | 12.7 mm |
| Grenzdrehzahl | 18000 rpm |
| Dynamische Belastung | 7.44 kN |
| Statische Belastung | 10.1 kN |
| Verpackung | 1 |

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE