


# Kegelrollenlager 2559-2525-TIMKEN - 2559-2525-TIMKEN

<https://www.123kugellager.at/kugellager-gehauselager/zylinderrollenlager/kegelrollenlager/2559-2525-timken>



Dimensions	Abmessung und Filter Dimension	Abmessung und Filter Dimension	
d - Bore	30.163 mm 1.1879 in	k - Case Backhoe "to Case" Radius	0.762 mm 0.030 in
D - Cup Outer Diameter	72.022 mm 2.836 in	r - Cup Backhoe "to Case" Radius <sup>2</sup>	0.76 mm 0.030 in
B - Case Width	25.267 mm 0.9943 in	Aa - Cup Front Face Backing Diameter	36.48 mm 1.434 in
C - Cup Width	19.050 mm 0.7500 in	Aa - Cup Back Face Backing Diameter	37.06 mm 1.459 in
T - Skating Width	23.813 mm 0.9375 in	Da - Cup Front Face Backing Diameter	66.00 mm 2.601 in
<b>Basic Load Ratings</b>		Db - Cup Back Face Backing Diameter	62.99 mm 2.48 in
C90 - Dynamic Radial Rating (90 million revolutions) <sup>4</sup>	4850 lbf 21 780 N	Ab - Cage Case Front Face Clearance	1.5 mm 0.06 in
C3 - Dynamic Radial Rating (3 million revolutions) <sup>4</sup>	18462 lbf 82700 N	Aa - Cage Case Back Face Clearance	0.5 mm 0.02 in
C0 - Static Radial Rating	31300 lbf 14000 N	a - Effective Center Location <sup>3</sup>	0.5 mm 0.02 in
C <sub>app</sub> - Dynamic Thrust Rating (90 Million revolutions) <sup>4</sup>	2280 lbf 10200 N		
<b>Factors</b>			
K - Factor <sup>7</sup>	2.54		
v - ISO Factor <sup>8</sup>	0.27		
Y - ISO Factor <sup>8</sup>	2.19		
G2 - Heat Generation Factor (Stiller - Baswell)	23.6		
G3 - Heat Generation Factor (Stiller - Baswell)	8.6		
G4 - Geometry Factor	0.0676		

## PRODUKTMERKMALE

Marke	TIMKEN
N° Ean13	3616060668097
Innendurchmesser	30.163 mm
Innendurchmesser	1 3/16" inch
Außendurchmesser	72.022 mm
Außendurchmesser	2.836" inch
Dicke	23.813 mm
Dicke	15/16" inch
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE