

Stehlagereinheiten / Flanschlagereinheiten 2 loch P2BSS-40M-YTPSS-SKF - P2BSS-40M-YTPSS-SKF

<https://www.123kugellager.at/kugellager-gehauselager/gehauselager/stehlagereinheiten-flanschlagereinheiten-2loch/p2bss-40m-ytpss-skf>

Données de calcul		
Charge dynamique de base	C	24.7 kN
Charge statique de base	C ₀	19 kN
Limite de fatigue	P ₀	0.8 kN
Vitesse limite		2800 rpm
Compliance with standard		Not standardized
Material		Stainless steel
Sealing solution		Outer seals
Dimensions		
D		40 mm
D ₁		51.8 mm
D ₂		49 mm
D ₃		53 mm
D ₄		51.5 mm
B		49.2 mm
B ₁		10 mm
H		99 mm
H ₁		49.2 mm
H ₂		19 mm
J		135.5 mm
J ₁	max.	146 mm
J ₂	min.	126 mm
L		174.5 mm
N		24.5 mm
N ₁		14.5 mm
s ₁		30.2 mm
Plots de centrage		
G		12 mm
G		0.5 in

PRODUKTMERKMALE

Marke	SKF
N° Ean13	3616060837707
Durchmesser der Welle	40 mm
Anzahl der Befestigungen	2
Befestigung	Exzentrischer Klemmring
Befestigungsabstand	135.5 mm
Material	INOX
Gewicht	1990 g
Verpackung	1
Standard	Ohne Standard

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE