

Zylinderrollenlager NA4920-JTEKT - NA4920-JTEKT

<https://www.123kugellager.at/kugellager-gehauselager/zyylinderrollenlager/zyylinder/na4920-jtekt>

Machined ring needle roller bearings **Koyo**
F_W 29 ~ 37 mm

With inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. Without inner ring | |
|--------------------------|-----|-----|----|-------------------------|---------------------|--|--------------------|-----------------------------------|-------------|
| F _w | d | D | B | C _r | C ₁₀ | Oil lub. | | | |
| 115 | 100 | 140 | 40 | 144.0 | 296.0 | 4 000 | | — | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | d ₁ min. | D ₁ max. | r _a max. | Without inner ring | With inner ring | |
| NA4920 | | | | 106.5 | 133.5 | 1 | 1.160 | 1.36 | IRM10011540 |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | JTEKT |
| N° Ean13 | 3663952484228 |
| Innendurchmesser | 100 mm |
| Außendurchmesser | 140 mm |
| Dicke | 40 mm |
| Gewicht | 1860 g |
| Verpackung | 1 |

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE