


Nadelhülsenlager BK2538-JTEKT - BK2538-JTEKT

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/bk2538-jtekt>

Boundary dimensions



Metric series with cage assembly

| Bearing No. | Boundary dimensions(mm) | | | | | Basic load ratings(kN) | | Fatigue load limit(kN) | Limiting speeds(min-1) | |
|-------------|-------------------------|----|----|----------------------|----------------------|------------------------|-----------------|------------------------|------------------------|----------|
| | Fw | D | C | C _w (min) | C _w (max) | C _r | C _{0r} | | Grease lub. | Oil lub. |
| BK2538 | 25 | 32 | 38 | 35.3 | 1 | 35.3 | 66.9 | 10.6 | 8500 | 13000 |

PRODUKTMERKMALE

| | |
|----------------------|---------------|
| Marke | JTEKT |
| N° Ean13 | 3616060629388 |
| Innendurchmesser | 25 mm |
| Innendurchmesser | 0.984" inch |
| Außendurchmesser | 32 mm |
| Außendurchmesser | 1.26" inch |
| Dicke | 38 mm |
| Dicke | 1.496" inch |
| Grenzdrehzahl | 8500 rpm |
| Dynamische Belastung | 35.3 kN |
| Statische Belastung | 66.9 kN |
| Verpackung | 1 |

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE