

# Nadelhülsenlager BAM1216-IKO - BAM1216-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/bam1216-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g	
	Standard	Mass (Ref.) g	Closed end											
19.050 (3/4)	---	---	---	---	---	---	---	---	---	---	---	---	---	
Boundary dimensions		mm(inch)		Standard mounting dimensions			mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed <sup>(1)</sup>	
$F_w$	$D$	$C$	$B$	Shaft dia. h6	Housing bore dia. J7	Max.	Min.	Max.	Min.	N	N	rpm	Assembled inner ring	
19.050	25.400	25.40(1.000)	1.3	19.050	19.037	25.412	25.391	16 300	25 500	20 000	IRB 816-1			

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173030
Innendurchmesser	19.05 mm
Innendurchmesser	3/4" inch
Außendurchmesser	25.4 mm
Außendurchmesser	1" inch
Dicke	25.4 mm
Dicke	1" inch
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE