



# Nadelhülsenlager BAM1414-IKO - BAM1414-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/bam1414-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g				
	Standard	Mass (Ref.) g	Closed end														
22.225 (7/8)	—	—	—	—	—	—	—	—	—	—	—	—	—				
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed <sup>(1)</sup>		Assembled inner ring	
$F_w$	$D$	$C$	$h_6$	Shaft dia.	Housing bore dia.												
				Max.	Max.	Min.	Max.	Min.									
22.225 (7/8)	28.575 (1 1/4)	22.22 (.875)	2.8	22.225	22.212	28.587	28.566			15 300	25 500	18 000					IRB 1014

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173146
Innendurchmesser	22.23 mm
Außendurchmesser	28.58 mm
Dicke	22.22 mm
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE