



# Nadelhülsenlager BAM146-IKO - BAM146-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/bam146-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

Shaft dia. mm (inch)	Identification number			Identification number			Mass (Ref.) g	Grease retained Mass (Ref.) g	
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end			
22.225 (7/8)	—	—	—	—	—	—	<b>BAM 146</b>	13.8	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed <sup>(1)</sup>	Assembled inner ring
$F_w$	$D$	$C$	Shaft dia. h6	Housing bore dia. J7	Max.	Min.	$C$	$C_0$	$C_0$	rpm		
22.225	28.575	9.521	22.225	22.212	28.587	28.566	5 430	6 740	18 000	IRB 106		

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173184
Innendurchmesser	22.23 mm
Außendurchmesser	28.58 mm
Dicke	9.52 mm
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE