

Nadelhülsenlager BAM1816-IKO - BAM1816-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/bam1816-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Standard			Closed end			Mass (Ref.) g			Grease retained g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g			
28.575 (1 1/8)	—	—	—	—	—	—	—	—	—	—	—
Identification number											
BAM 1816											
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed(*)	Assembled inner ring	
F_w	D	C	Shaft dia. mm	Housing bore dia. mm	J_7	C	C_0	rpm	IRB 1416		
28.575 1 1/8	34.925 1 3/8	25.40 1.000	28.575 Max. 28.562 Min.	34.939 Max. 34.914 Min.	—	20 500	40 900	13 000	—		

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173344
Innendurchmesser	28.58 mm
Außendurchmesser	34.93 mm
Dicke	25.4 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE