


Nadelhülsenlager BAM1910-IKO - BAM1910-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/bam1910-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
30.162 (1 1/8)	---	---	---	---	---	---	---	---	---	---	---	---	---
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring				
F _w	D	C	Shaft dia. h _s	Housing bore dia. h _{J7}	Max.					Min.	Max.	Min.	N
30.162 (1 1/8)	38.100 (1 1/2)	15.88 (5/8)	30.162	30.146	38.114	38.089	15 000	22 500	12 000	---			

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173382
Innendurchmesser	30.16 mm
Außendurchmesser	38.1 mm
Dicke	15.88 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE