


Nadelhülsenlager BAM45-IKO - BAM45-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/bam45-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g				
6.350 ($\frac{1}{4}$)	—	—	—	—	—	—	—	BAM 45	2.7	—	—	—
Boundary dimensions mm (inch)		Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring			
F _w	D	C	h ₈ Max. Min.	J ₇ Max. Min.								
6.350 ($\frac{1}{4}$)	11.112 ($\frac{7}{16}$)	7.921 ($\frac{5}{16}$)	6.350 Max. 6.341 Min.	11.122 Max. 11.104 Min.	1 510	1 120	55 000	—				

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173412
Innendurchmesser	6.35 mm
Außendurchmesser	11.11 mm
Dicke	7.92 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE