


Nadelhülsenlager BAM810-IKO - BAM810-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/bam810-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
12.700 ($\frac{1}{2}$)	—	—	—	—	—	—	—	BAM 810	9.6	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring	
F _w	D	C	Shaft dia. h8	Housing bore dia. J7	h	b					
12.700 ($\frac{1}{2}$)	17.462 ($\frac{9}{16}$)	15.881 (625)	1	12.700	12.689	17.472	17.454	6 350	8 380	30 000	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173566
Innendurchmesser	12.7 mm
Außendurchmesser	17.46 mm
Dicke	15.88 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE